

Fire Shutters Rolling Doors



SPACE-SAVING DESIGN AND PROTECTION.

Certified for installation to sheetrock, steel, and masonry construction, C.H.I.'s U.L. labeled fire shutter utilizes a space-saving design with performance-proven engineering features for maximum eye appeal and fire protection.

MODEL SELECTION CHART

	Model	Slat Profile	Slat Material	Gauge	Fire Rating	Max. Size ²	Colors ¹ / Finishes ¹
Flat Slat	7522	F1.5	Steel	22 Gauge	3/4 Hr., 1-1/2 Hr. or 3 Hr.	13'0" x 8'4"	Gray, White, Galvanized, PC
	7566	F1.5	Stainless Steel				#4 Finish

¹ Refer to your local Dealer for exact color or finish match. ² Sizes displayed as width x height. Consult factory for larger sizes.


PC = doors available in 188 powder coated options.

CURTAIN PROFILES




Flat [F1.5]


MOUNTING OPTIONS




Steel




Wood



Masonry



Over 2-Layer
Fire Rated Drywall



BEST MARKET USES

Divide Commercial Spaces • Automotive/Service Centers •
Commercial Food Service



WANT TO SEE MORE?
Visit: chiod.com/commercial-doors/rolling-fire-shutters