								Micro-Grooved	Sandwich Door	3216	
										•	
								Section Thickness: 2"			
							Section Heights: 18", 21", 24"				
Interior Elevation Exterior Elevation											
									Panel Material: Hot dipped galvanized steel		
								26 gauge exterior / 27 gauge interior			
Joint Detail						1_ T					
Tongue and groove design			$\wedge$					Panel Profile: Woodgrain textured exterior with			
with flexible gasket between sections			0					four evenly spaced micro-grooves / Woodgrain			
				/				flush interior			
			o /			d	oor height				
		<i>х</i> ()					sections high	End Stiles: 20 gauge white painted galvanized			
								steel, full height of section			
	$) \vdash$							Insulation OFO free wethers forward in alcost			
	, )	0	Q//						Insulation: CFC free urethane foamed in place		
							R-Value 17.54 / U-Value 0.057 / U-Factor* 0.19 Rails have full thermal break				
Hinge Detail			one section			Rails nave full thermal break					
•								Air Infiltration*: (	0.10 cfm/ft <sup>2</sup> with vinvl doo	r stop /	
Graduated end hinges ≥ 16'-3" wide = double end hinges							Air Infiltration*: 0.10 cfm/ft <sup>2</sup> with vinyl door stop / 0.17 cfm/ft <sup>2</sup> with clip on jamb seal				
minimum 14 gauge								0.17 CIII/It Wit			
one panel —								Color: Polvester	primer and top coat in C	НΙ·	
									White, Almond, Sandstone, Brown, Black, Gray,		
door width / par					iels wide				RAL# powder-coating exterior / White, RAL#		
									powder-coating interior		
									Logo printing available on exterior & interior		
		D	aar Width Danala	Wide	Door Hoight	Soctions Liek					
Bottom Seal Detail 08'-00" to 09'-05"				Door Height Sections High   2 07'-00" to 08'-00" 4				Glazing Options: 1"; Clear, Tinted, Tempered in			
Bottom Seal Detail			6" to 12'-11" 3		08'-03" to 10'-00" 5			24"x6", 24"x12", 34"x16" / Full-View Aluminum			
TPE astragal in 13'-00" to 16'-05"   aluminum retainer 16'-06" to 20'-02"				4 10'-03" to 12'-00" 6 5 12'-03" to 14'-00" 7			(34"x16" n/a in end panels on 10', 14', 18', 22' wide doors & 18", 21" sections)				
20'-03" to 24'-02"			14'-03" to 16'-00" 8			(Full-View Aluminum frame to match size and panel layout of steel section)					
24'-03" to 26'-02" 8 26'-03" to 30'-02" 10					16'-03" to 18'-00" 18'-03" to 20'-00"	9 10		(Check Full-View Alumi	inum door for color, glass, end stile ar	nd rail options)	
30'-03" to 32'-02" 12 Available in 3" height increments								IECC compliant			
Available in 1" width increments								*IECC testing details do not apply to doors with windows and/or exhaust ports			
				Cc	ntact C.H.I. for special siz	ing outside of liste	ed pricebook charts		product, contact C.H.I. for options	REV. July/2018	
Door Mark	Door Width	Door Height	Door Type	Project Name				Prepared By			
Door Quantity	Opening Width	Opening Height	Jamb Type	Operation				Date			
,, ,											
Quote Number	Panels Wide	Sections High	Color	Door Company				Sheet	OVERHEAD D	0 0 R S	
Architect				Contractor				Januar objeba a	com   1485 Sunrise Drive, Arthur, IL 6	1011	
									om   1485 Sunnse Drive, Arthur, IL 6 om   Phone: (800) 590-0559   Fax: (80		